

## IN THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) Apparatus for assaying an analyte in blood in a blood vessel below a  
 5 patient's skin comprising:

at least one light source controllable to transmit light into tissue below the skin  
 through at least one first region on the skin;

- 10 modulating apparatus that modulates the flow of blood through the blood vessel;  
 at least one light detector that receives a portion of the transmitted light that reaches at  
 least one second region on the skin after propagating through the blood vessel and generates  
 signals responsive to the received light and the modulation; and

a controller;

- wherein the controller controls the at least one light source to transmit light at at least  
 one wavelength that interacts with blood and at at least one wavelength that interacts with the  
 15 analyte and uses the signals responsive to the light that interacts with the blood to determine a  
 location for the blood vessel and the determined location and signals responsive to the light to  
 assay the analyte.

2. (Original) Apparatus according to claim 1 wherein the controller controls the at least one  
 20 light source and/or the at least one detector to transmit light between at least two pairs of first  
 and second regions on the skin for which the distance between the first and second regions in  
 one pair is different from that of the other pair.

- 25 3. (Cancelled)

4. (Currently amended) Apparatus according to claim ~~3-1~~ wherein the modulation apparatus  
 comprises an ultrasound transmitter that illuminates the blood vessel with ultrasound.

- 30 5. (Currently amended) Apparatus according to claim ~~3-or claim 4~~ wherein the modulation  
 apparatus comprises a source of electrical power that applies a time varying electric field to a  
 region of the patient's body that causes recurrent tensing and relaxation of muscles that affect  
 the size of the blood vessel.

6. (Currently amended) Apparatus according to ~~any of claims 3-5~~claim 1 wherein the modulation apparatus comprises a mechanical resonator that applies a time varying pressure to a region of the blood vessel.
- 5 | 7. (Currently amended) Apparatus according to claim 1 ~~any of claims 3-6~~ wherein the controller determines the location responsive to the modulation of the signals.
8. (Currently amended) Apparatus according to claim 1 ~~any of claims 3-7~~ wherein the controller assays the analyte responsive to the modulation of the signals.
- 10 | 9. (Currently amended) Apparatus according to claim 1 ~~any of the preceding claims~~ and comprising a light pipe coupled to each of the at least one light source that transmit light from the light source to the at least one first region.
- 15 | 10. (Currently amended) Apparatus according to claim 1 ~~any of the preceding claims~~ and comprising a light pipe coupled to each of the at least one light detector that transmit light from the at least one second region to the detector.
- 20 | 11. (Currently amended) Apparatus according to claim 1 ~~any of the preceding claims~~ wherein the at least one detector comprises a plurality of detectors.
12. (Original) Apparatus according to claim 11 wherein the detectors comprise pixels in a CCD
- 25 | 13. (Original) Apparatus according to claim 12 and comprising a lens that collects light from the at least one second region and focuses the light on the CCD.
14. (Currently amended) Apparatus according to claim 1 ~~any of the preceding claims~~ wherein the light source comprises a single light source.
- 30 | 15. (Currently amended) Apparatus according to claim 1 ~~any of the preceding claims~~ wherein the light source is controllable to be moved so as to illuminate different first regions on the skin.

16. (Currently amended) Apparatus according to ~~any of the preceding claims~~claim 1 wherein the analyte is glucose.

5 17. (Currently amended) A method for assaying an analyte in blood in a blood vessel below a patient's skin comprising:

modulating the flow of blood through the blood vessel;

transmitting light at at least one wavelength that interacts with blood and is modulated responsive to the modulation and at at least one wavelength that interacts with the analyte into

10 tissue below the skin through at least one first region on the skin;

generating signals responsive to a portion of the transmitted light at each of the at least one wavelengths that reaches at least one second region on the skin after propagating through the blood vessel;

15 using the signals responsive to the light that interacts with the blood to determine a location for the blood vessel and the determined location and signals responsive to the light to assay the analyte.